

TIMBER SPECIFICATIONS

- ALL UNITS ARE SECTIONAL & SUPPLIED WITH FELT, TRIMS & ALL NECESSARY FIXINGS
- 16mm x 125mm HIGH QUALITY T&G SHIPLAP WEATHERBOARD
- 38mm x 50mm PLANED ROUND EDGE FRAMEWORK
- HEAVY DUTY GLASS-FIBRE REINFORCED GREEN MINERAL FELT
- FINISH – PRESSURE TREATED AGAINST ROT (TANALIZED)
- ALL IRONMONGERY IS GALVANISED OR SIMILARLY COATED
- 3mm CLEAR ACRYLIC USED IN ALL FIXED WINDOWS
- HOUSINGS CAN BE INSULATED AND LINED
- UNITS CAN BE MANUFACTURED TO CUSTOMERS OWN SIZES
- (a £35 nominal fee is charged for alterations other than items listed on our Extra's List)

	KENNELS				CAT CHALETs			AVIARIES					SMALL ANIMAL HOUSINGS					
	CABIN (small)	CABIN (large)	COSY	LOFTY	RICHMOND	HILTON	MANOR	MALVERN	PERSHORE	TEWKESBURY	GLOUCESTER	WORCESTER	SNUG	RABBIT HUTCH	PET ARK	PET RUNS	BANBURY POULTRY HOUSE	STRATFORD POULTRY HOUSE
HEIGHT*	23"- 25"	31.5"- 35"	44"- 49"	62"- 67"	65"- 72"	72"- 83"	72"- 88"	71"- 75"	71"- 75"	71"- 75"	71"- 75"	71"- 76"	44"- 48"	44"	6' ~ 27" 8' ~ 33"	25"	44"- 48"	71"- 76"
FELT	*	*	*	*	*	*	*	*	*	*	*	*	*	*			*	*
FIXED WINDOW			vent	vent	*	*	*	*	*	*	*	*	*				vent	vent & fixed window
MESH			2"x 2" 10g	2"x 2" 10g	1"x 1" 16g	1"x 1" 16g	1"x 1" 16g	1/2"x 1" 19g	1/2"x 1" 19g	1/2"x 1" 19g	1/2"x 1" 19g	1/2"x 1" 19g	1"x 1" 16g	1"x 1" 16g	1"x 1" 16g	1"x 1" 16g		1"x 1" 16g
SAFETY PORCH					optional	optional	optional	optional	optional	*	*	*	optional					
SLIDING HATCH			*	*	cat flap	cat flap	cat flap	*	*	*	*	*	*		*		*	*
HATCH OPENING	8"x 12"	11"x 17"	11"x 17"	11"x 17"	6"x 7"	6"x 7"	6"x 7"	5"x 7"	5"x 7"	5"x 7"	7"x 7"	7"x 7"	6"x 7"		7"x 7"		7"x 7"	7"x 7"

*All height measurements to eaves. All sizes listed are nominal and are subject to production variation. Our Policy is one of constant improvement and all specifications may be changed without prior notice.

"STRONGHOLD" STEEL PANEL SPECIFICATIONS

1" x 1" SQUARE TUBE FRAME CLAD WITH 2" x 2" x 10g WELDMESH

ALL "STRONGHOLD" PANELS ARE HOT DIPPED GALVANISED AFTER MANUFACTURE TO B.S. 729

PANEL TO PANEL FIXINGS INCLUDED AS STANDARD - (2 x 8mm bolts per panel)

All Gate Apertures are 871mm (3') wide

All Gates are hinged on the left and open inwards unless otherwise specified



ALTERNATIVE INFILLS

ANY "STRONGHOLD" PANEL CAN BE MANUFACTURED WITH THE LOWER SECTION CLAD IN 20g (1mm) GALVANISED STEEL SHEET (POP RIVETED TO GALVANISED FRAME)